



12 HOLES EQ. SP. TO STRADDLE ϕ
ON 18.750\"/>

- NOTES:**
- VALVES ARE MANUFACTURED IN ACCORDANCE WITH ANSI/AWWA C517-09, "RESILIENT-SEATED CAST IRON ECCENTRIC PLUG VALVES."
 - END FLANGE DIMENSIONS AND DRILLING ARE IN ACCORDANCE WITH ASME/ANSI B16.1, CLASS 125 FOR CAST IRON PIPE FLANGES AND FLANGE FITTINGS.
 - PAINT: BLUE - SEMI-GLOSS METAL PRIMER
 - ELASTOMERS AVAILABLE: BUNA-N
EPDM
NEOPRENE
VITON
 - WEIGHTS: VALVE - 750 LBS
GEAR - 60 LBS

ALL DIMENSIONS IN INCHES
UNLESS OTHERWISE NOTED

19	CHAINWHEEL ASSY	WHEN SPECIFIED
18	GEAR	COMMERCIAL
17	KEY	STEEL
16	PIPE PLUG	IRON
15	CAPSCREW	STEEL, ZINC PLATED
14	COVER PLATE	A126 CLB
13	CAPSCREW	STEEL, ZINC PLATED
12	SEAL	SEE NOTE 4
11	CAPSCREW	STEEL, ZINC PLATED
10	SEAL	SEE NOTE 4
9	HEX NUT	STEEL, ZINC PLATED
8	STUD	STEEL, ZINC PLATED
7	PACKING GLAND	A126 CLB
6	PACKING	V-RING, SEE NOTE 4
5	THRUST BEARING	PTFE
4	RADIAL BEARING	PERM. LUBRICATED 316SS
3	PLUG	A536 65-45-12/NOTE 4
2	CAP	A126 CLB
1	BODY	A126 CLB/NICKEL SEAT
NO.	PART NAME	MATERIAL

PARTS LIST

HOMESTEAD[®] VALVES
A DIVISION OF OLSON TECHNOLOGIES, INC.
160 WALNUT ST. ALLENTOWN, PA. 18102 (610) 770-1100
WWW.HOMESTEADVALVE.COM

F	S1600	RH		1/19/15	TITLE	14" E126 - GEAR OPERATED ECCENTRIC PLUG VALVE
E	S1298	RH	DED	1/25/11		
D	S1226	RH	DED	4/19/10		
C	S1017	RH	DED	7/19/08	NUMBER	
REV	ISSUE	BY	APPR	DATE		

SK-4055