


HOMESTEAD SERIES 821 AWWA BUTTERFLY VALVE

## GENERAL SPECIFICATIONS:

- 1. MANUFACTURED IN ACCORDANCE WITH AWWA C504, CLASS 150B, LATEST REVISION.
- 2. FLANGES CONFORM TO AWWA C111/A21.11 MECHANICAL JOINT, LATEST REVISION.
- 3. BODY AND DISC TO BE COATED WITH "NSF 61 APPROVED" FUSION-BONDED EPOXY.

## NOTES:

1. ELASTOMERS AVAILABLE: NITRILE (BUNA-N) EPDM



21	NUT	STEEL, ZINC PLATED		
20	B□LT	STEEL, ZINC PLATED		
19	SCREW	STEEL, ZINC PLATED		
18	ACTUAT□R	MANUAL		
17	KEY	CARBON STEEL		
16	SEAT	SEE NOTE 1		
15	NUT	304SS		
14	WASHER	304SS		
13	PIN	304SS		
12	SCREW	STEEL, ZINC PLATED		
11	BOTTOM COVER	CARBON STEEL		
10	THRUST WASHER	NYLON		
9	PACKING	V-RING, SEE N□TE 1		
8	LOWER BEARING	NYLON		
7	RETAINING RING	CARBON STEEL		
6	WASHER	304SS		
5	PACKING	V-RING, SEE NOTE 1		
4	UPPER BEARING	NYLON		
3	SHAFT	316SS		
2	DISC	A536 65-45-12/316SS		
1	B□DY	A536 65-45-12		
ND.	PART NAME	MATERIAL		
PARTS LIST				

## - TINCTO E101

HOMESTEAD VALVES
A DIVISION OF OLSON TECHNOLOGIES, INC.
160 WALNUT ST. ALLENTOWN, PA. 18102 (610) 770-1100

					TITLE	16"-24" SERIES 821
						M.J. BFV ASSY. W/MANU
В	\$1314	RH		03/25/19		ACTUATOR & 2" NUT
Α	S914	TC	DED	06/04/07	NUMBER	SK-5007
REV	ISSUE	ΒY	APPR	DATE		2/-2007

VULCANIZED ELASTOMER SEAT  SECTION 'A-A'	2" SQ. AWWA NUT — TURN CLOCKWISE TO CLOSE VALVE
A' A'	C' DIA. TYP.  SLOTTED ON 24"
<u> </u>	YALVE ONLY  'G' DIA THRU 'H' HOLES EQL. SP. ON 'I' DIA. B.C.

(13)(14)(15)

This drawing and its design are the property of OLSON TECHNOLOGIES. This drawing is loaned to you subject to the condition that it shall not be reproduced, copied, lent or otherwise disposed of, directly or indirectly. It shall not be used to furnish any information for the making of drawings, prints, or apparatus, or parts thereof, except where otherwise specifically provided for by contract agreement with OLSON TECHNOLOGIES.

- 24" VALVE ONLY

(8)

(5)

(1)

(20) (21)

- 316 SS

DISC EDGE