



- HOMESTEAD SERIES 840 AWWA BUTTERFLY VALVE
- GENERAL SPECIFICATIONS:**
1. MANUFACTURED IN ACCORDANCE WITH AWWA C504, CLASS 150B, LATEST REVISION.
 2. FLANGES CONFORM TO ANSI B16.1 "CAST IRON PIPE FLANGES AND FLANGE FITTINGS", CLASS 125.
 3. BODY AND DISC TO BE COATED WITH: "NSF 61 APPROVED" FUSION-BONDED EPOXY
 4. DIRECTION TO OPEN VALVE IS COUNTER-CLOCKWISE

- NOTES:**
1. ELASTOMERS AVAILABLE IN EPDM AND NITRILE (BUNA-N)

NO.	PART NAME	MATERIAL
17	O-RING	BUNA-N
16	COVER PLATE	DI 65-45-12
15	THRUST PLATE	BRONZE
14	SCREW, SKT. HD.	TY316 SS
13	SEAT CLAMP RING	TY316 SS
12	SEAT	BUNA-N
11	HEX NUT	TY316 SS
10	DISC PIN RETAINER	TY316 SS
9	DISC PIN	TY316 SS
8	SCREW, HEX CAP	TY316 SS
7	PACKING GLAND	DI 65-45-12
6	PACKING	BUNA-N
5	BEARINGS	BRONZE
4	BOTTOM SHAFT	TY316 SS
3	TOP SHAFT	TY316 SS
2	DISC	DI 65-45-12 / 316SS EDGE
1	BODY	DI 65-45-12

PARTS LIST			
HOMESTEAD VALVES A DIVISION OF OLSON TECHNOLOGIES, INC. 160 WALNUT ST. ALLENTOWN, PA. 18102 (610) 770-1100			
		TITLE	30" SERIES 840 BARE STEM 150B AWWA BFV ASSEMBLY
A	S1897	ND	2/25/20
REV	ISSUE	BY	APPR DATE
			NUMBER SK-5013

This drawing and its design are the property of OLSON TECHNOLOGIES. This drawing is loaned to you subject to the condition that it shall not be reproduced, copied, lent or otherwise disposed of, directly or indirectly. It shall not be used to furnish any information for the making of drawings, prints, or apparatus, or parts thereof, except where otherwise specifically provided for by contract agreement with OLSON TECHNOLOGIES.