



(8) .875" DIA DRILL THRU
EQ SP ON 8.50" DIA B.C.

NOTES:

- VALVES ARE MANUFACTURED IN ACCORDANCE WITH ANSI/AWWA C517-09, "RESILIENT-SEATED CAST IRON ECCENTRIC PLUG VALVES."
- END FLANGE DIMENSIONS AND DRILLING ARE IN ACCORDANCE WITH ASME/ANSI B16.1, CLASS 125, "CAST IRON PIPE FLANGES AND FLANGE FITTINGS."
- PAINT: BLUE - SEMI-GLOSS METAL PRIMER
- ELASTOMERS AVAILABLE: BUNA-N
EPDM
NEOPRENE
VITON

18	CHAINWHEEL ASSY	WHEN SPECIFIED
17	CAP SCREW	STEEL, ZINC PLATED
16	KEY	STEEL
15	GEAR	COMMERCIAL
14	SEAL	SEE NOTE 4
13	PIPE PLUG	A126 CLB
12	HEX NUT	STEEL, ZINC PLATED
11	STUD	STEEL, ALLOY
10	PACKING GLAND	A126 CLB
9	PACKING	V-RING, SEE NOTE 4
8	RADIAL BEARING	PERM. LUBRICATED 316SS
7	THRUST BEARING	PTFE
6	THRUST BEARING	PTFE
5	RADIAL BEARING	PERM. LUBRICATED 316SS
4	CAP SCREW	STEEL, ZINC PLATED
3	MTG BRACKET	A126 CLB
2	PLUG	A126 CLB/SEE NOTE 4
1	BODY	A126 CLB/NICKEL SEAT
NO.	PART NAME	MATERIAL

PARTS LIST

HOMESTEAD® VALVES
A DIVISION OF OLSON TECHNOLOGIES, INC.
160 WALNUT ST. ALLENTOWN, PA. 18102 (610) 770-1100

				TITLE
				5" ECCENTRIC PLUG VALVE w/ GEAR
A	S1600	RH	10/21/15	NUMBER
REV	ISSUE	BY	APPR	DATE
				SK-4156